

# ActualCollection

## WELCOME TO ACTUALCOLLECTION

ActualCollection dumps, higher pass rate



ActualCollection is a website offering the latest and valid actual exam dump to make you go through the actual test with a high score.



### Quality and Value

ActualCollection Practice Exams are written to the highest standards of technical accuracy, using only certified subject matter experts and published authors for development - no all dumps.



### Tested and Approved

We are committed to the process of vendor and third party approvals. We believe professionals and executives alike deserve the confidence of quality coverage these authorizations provide.



### Easy to Pass

If you prepare for the exams using our ActualCollection testing engine, it is easy to succeed for all certifications in the first attempt. You don't have to deal with all dumps or any free torrent / rapidshare all stuff.



### Try Before Buy

ActualCollection offers free demo of each product. You can check out the interface, question quality and usability of our practice exams before you decide to buy.

<http://www.actualcollection.com>

Actual dumps collection, higher pass rate

**Exam :** 000-543

**Title :** DB2 9.7 Application Development

**Vendors :** IBM

**Version :** DEMO

NO.1 Click the Exhibit button.

```
CREATE TABLE store(sid INTEGER, info XML);
INSERT INTO store VALUES (1,
'<storeinfo sid="1">
<name>Grocery A</name>
<items>
<fruit><name>Mango</name><price>1.20</price></fruit>
<fruit><name>Apple</name><price>0.50</price></fruit>
<dessert><name>Ice Cream</name><price>6.00</price></dessert>
</items>
</storeinfo>');
```

Given the statements shown in the exhibit, a user executes the query shown below:

```
XQUERY for $store in db2-fn:xmlcolumn('STORE.INFO')/storeinfo
```

```
let $items := $store/items/fruit, $count := fn:count($items)
```

```
return <itemcount>$count</itemcount>
```

What is the output?

- A. 2
- B. <itemcount>2</itemcount>
- C. <itemcount>1</itemcount>
- D. <itemcount>\$count</itemcount>

Answer: D

NO.2 An existing table has the definition shown below:

```
CREATE TABLE hr.employees (
empid INTEGER NOT NULL PRIMARY KEY,
deptno INTEGER,
authid VARCHAR(255),
salary DECIMAL (10,2),
commission DECIMAL (5,3) DEFAULT 0,
benefits XML )
```

Only members of the HR\_ADMIN group have privilege to SELECT, INSERT, UPDATE, or DELETE from

the HR.EMPLOYEES table. A Web-based application is under development that connects to the

database with a user's AUTHID and enables a user to see their record. No other records are visible.

Which type of database object can be created by a member of the HR\_ADMIN that provides the

necessary information without changing the privileges on the HR.EMPLOYEES table?

- A. trigger
- B. view
- C. alias
- D. index

Answer: B

NO.3 The table shown below contains a large number of financial transactions:

```
CREATE TABLE webstore.transactions (  
transaction_id INTEGER NOT NULL PRIMARY KEY,  
order_date TIMESTAMP NOT NULL,  
shipped_date TIMESTAMP,  
customer_id INTEGER NOT NULL,  
shipping_info XML NOT NULL,  
billing_info XML NOT NULL,  
invoice XML NOT NULL )
```

Only members of the AUDIT\_TEAM group have SELECT privilege on the WEBSTORE.TRANSACTIONS

table. For appropriate supply-chain management, members of the INVENTORY\_CONTROL group need

to see the INVOICE document for each transaction that has a NULL SHIPPED\_DATE, but are restricted

from seeing any shipping or billing information.

Which database object can a member of the AUDIT\_TEAM group create to enable the INVENTORY\_CONTROL group to access the information needed from WEBSTORE.TRANSACTIONS?

- A. alias
- B. sequence
- C. trigger
- D. view

Answer: D

NO.4 User USER1 successfully creates a table USER1.TABLE1 and successfully creates a package

USER1.PKG1 for an application containing the SQL shown below:

```
EXEC SQL UPDATE user1.table1 SET col1 = :hvar1 WHERE col1 IS NULL
```

Assuming user USER2 can connect to the database, but has no other relevant authorities, which

command must user USER1 issue to permit user USER2 to run the application?

- A. GRANT ALTER ON TABLE user1.table1 TO USER user2
- B. GRANT EXECUTE ON PACKAGE user1.pkg1 TO USER user2
- C. GRANT UPDATE ON TABLE user1.table1 TO USER user2
- D. GRANT BIND ON PACKAGE user1.pkg1 TO USER user2

Answer: B

NO.5 For which two database objects can an ALIAS be created? (Choose two.)

- A. schema
- B. trigger
- C. sequence
- D. module

Answer: CD

NO.6 Which object can be created to group together related procedures and user-defined functions that are used for tax calculations?

- A. collection
- B. module
- C. routine
- D. routine space

Answer: B

NO.7 The table shown below exists in the database:

```
CREATE TABLE team.workitems ( priority INTEGER, last_update TIMESTAMP, details XML )
```

User USER1 has CREATEIN authority on the TEAM schema and can SELECT from the TEAM.WORKITEMS table. An SQL routine is created that performs a positioned update using a cursor

declared as shown below:

```
DECLARE c_workitem CURSOR FOR SELECT priority, last_update FROM team.workitems FOR UPDATE;
```

Which additional privilege is required?

- A. EXECUTE privilege on TEAM schema
- B. ALTER privilege on TEAM.WORKITEMS table
- C. BINDADD privilege on TEAM schema
- D. UPDATE privilege on TEAM.WORKITEMS table

Answer: D

NO.8 You have created a stored procedure (MULTIRESULTS()) on the server which will return multiple result sets. While developing a PHP application using the IBM\_DB2 extension, you want to call the stored procedure. The code shown below will execute the stored procedure:

```
$stmt = db2_exec($conn, 'CALL multiResults()');
```

How can you fetch all of the result sets from \$stmt?

- A. Call db2\_fetch\_object(\$stmt) for the first result set; call db2\_next\_result(\$stmt) for more result sets.
- B. Call db2\_next\_result(\$stmt) for each result set.
- C. Call db2\_fetch\_object(\$stmt) for each result set.
- D. Call db2\_next\_result(\$stmt) for each result set; call db2\_fetch\_object(\$stmt) for each row in the result set.

Answer: A

NO.9 Which SQL procedure will retrieve all the rows from table T1 and make those rows available to the invoker as a result set?

A. CREATE PROCEDURE proc1()

```
DYNAMIC RESULTS SET 1
```

```
LANGUAGE SQL
```

```
SELECT * FROM t1
```

B. CREATE PROCEDURE proc1()

```
DYNAMIC RESULTS SET 1
```

```
LANGUAGE SQL
```

```
BEGIN
```

```
DECLARE c1 CURSOR WITH RETURN FOR SELECT * FROM t1;
```

```
OPEN c1;
```

```
END
```

C. CREATE PROCEDURE proc1()

```
DYNAMIC RESULTS SET 1
```

```
LANGUAGE SQL
```

```
RETURN (SELECT * FROM t1)
```

D. CREATE PROCEDURE proc1()

```
DYNAMIC RESULTS SET 1
```

```
LANGUAGE SQL
BEGIN
DECLARE c1 CURSOR FOR SELECT * FROM t1;
RETURN c1;
END
```

Answer: B

NO.10 You have set your data types as CHAR(10), VARCHAR(20). Given the operation shown below:

```
CHAR(10) UNION VARCHAR(20)
```

What will be the final data type?

- A. CHAR(200)
- B. VARCHAR(30)
- C. VARCHAR(20)
- D. CHAR(30)

Answer: C

NO.11 The statement below was used to create a cursor named CSR1:

```
DECLARE csr1 DYNAMIC SCROLL CURSOR FOR
SELECT * FROM employee;
```

After fetching all of the rows in the result set associated with cursor CSR1, which two statements can be

used to fetch the data starting at the end of the result set? (Choose two.)

- A. FETCH LAST
- B. FETCH PRIOR
- C. FETCH RELATIVE
- D. FETCH OFFSET

Answer: BC

NO.12 Which object can be invoked on a single invocation to return both output parameters and a result set

back to the invoking application?

- A. procedure
- B. module
- C. table function
- D. method

Answer: A

NO.13 An application must insert values into a column that has a TIMESTAMP data type.

What is a valid string representation of a TIMESTAMP?

- A. 2009.08.07.12.22.22.0000
- B. 2009-08-07 12:22:22.0000
- C. 07/08/2009-12:22:22:0000
- D. 07-08-2009 12.22.22.0000

Answer: B

NO.14 Click the Exhibit button.

```
CREATE TABLE s1.mytab (  
col1 INTEGER GENERATED ALWAYS AS IDENTITY,  
col2 INTEGER,  
col3 INTEGER,  
CHECK (col1+col3 < 500)  
)  
CREATE VARIABLE s1.var1 INTEGER DEFAULT (99)  
CREATE FUNCTION s1.add100 (p1 INT, p2 INT)  
RETURNS INTEGER  
LANGUAGE SQL  
DETERMINISTIC  
NOT FENCED  
BEGIN  
SET p1= p2+100;  
RETURN p1;  
END
```

Given the table, variable, and function definitions shown in the exhibit, which two statements contain a

valid invocation of the add100 function? (Choose two.)

- A. SELECT col1, outcol=add100(col2,col3) FROM mytab
- B. SET var1 = ABS(add100(1,99))
- C. SELECT col1, add100(col2,col3) AS outcol FROM mytab
- D. SELECT outcol.\* FROM TABLE(add100(col2,col3)) AS outcol

Answer: BC

NO.15 A database contains a table and a view declared as shown below:

```
CREATE TABLE s1.t1 ( c1 INTEGER, c2 CHAR(20) );  
CREATE VIEW s1.v1 AS SELECT * FROM s1.t1;
```

A system administrator successfully executes the following code:

```
GRANT CONNECT, IMPLICIT_SCHEMA ON DATABASE TO user1;
```

```
GRANT INSERT ON TABLE s1.t1 TO user1;
```

```
GRANT CONTROL ON s1.v1 TO user1;
```

Which SQL statement does user USER1 have privileges to execute?

A. UPDATE s1.t1 SET c1 = 2 WHERE c1 IS NULL

B. CREATE VIEW user1.v2 AS SELECT \* FROM s1.v1

C. CREATE PUBLIC ALIAS a1 FOR s1.v1

D. SELECT \* FROM s1.t1 WHERE c2 < 100

Answer: B

NO.16 A database contains two tables with the same definition and authorities:

PRODUCTION.SALESDATA

and TEST.SALESDATA. The PRODUCTION.SALESDATA table contains business-critical information

that is constantly changing; the TEST.SALESDATA table contains a snapshot of the PRODUCTION.SALESDATA table. Business rules require that applications under development access

the TEST.SALESDATA table until ready for deployment. Once an application is deployed, it accesses the

PRODUCTION.SALESDATA table.

Which object can be used to simplify switching between the TEST.SALESDATA and PRODUCTION.SALESDATA tables without having to re-code the application?

A. trigger

B. procedure

C. alias

D. sequence

Answer: C

NO.17 In a query, which clause can reference a CLOB data type?

A. an ORDER BY clause

B. a GROUP BY clause

C. a WHERE clause

D. a DISTINCT clause

Answer: C

NO.18 Click the Exhibit button.

```
CREATE FUNCTION deptemployees (idept VARCHAR(3))
```

```
RETURNS TABLE (empno CHAR(6),
```

```
firstname VARCHAR(12),  
lastname VARCHAR(15)  
LANGUAGE SQL  
READS SQL DATA  
NO EXTERNAL ACTION  
DETERMINISTIC  
RETURN  
SELECT empno, firstnme, lastname  
FROM employee  
WHERE workdept = deptemployees.idept;
```

Referring to the exhibit, what contains the proper way to invoke the DEPTEMPLOYEES() user-defined

function to return all of the employees that work in department D11?

- A. SELECT \* FROM TABLE(deptemployees('D11'))
- B. SELECT \* FROM deptemployees('D11')
- C. SELECT \* FROM deptemployees('D11') AS D11dept
- D. SELECT \* FROM TABLE(deptemployees('D11')) AS D11dept

Answer: D

NO.19 Which statement is true of an application that only uses static SQL?

- A. The authorization ID of program creator is used to qualify explicitly qualified table references on a DROP statement.
- B. Static SQL uses SQLDA to determine the number of rows successfully fetched on a FETCH statement.
- C. The authorization ID of application creator is used to qualify implicitly qualified view references on an UPDATE statement.
- D. The authorization ID of application invoker used by DB2 to perform authorization checking of an embedded OPEN statement during execution.

Answer: C

NO.20 Which condition will prevent a developer from using the DB2 Call Level Interface in an application?

- A. The developer must control the cursor names to comply with company naming standards.
- B. An SQL precompiler is not available to the developer.
- C. The application must create an external scalar function with the CREATE FUNCTION

statement.

D. The DECLARE CURSOR statement needs to be used.

Answer: D